

Outdoor wall steplight luminaire

Minimum thickness for surface installation / Recessed installation flush with the wall using backbox optional accessory

Material: low copper content die-cast aluminium

UV resistant polycarbonate diffuser, recessed for an effective reduction of direct glare

Light source: mains voltage LED module, compatible with phase-cut dimmers

Rear cable entry / Spacer optional accessory for side cable entry

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

**24V** 24V low voltage

|                                          |                              |
|------------------------------------------|------------------------------|
| Dimensions                               | <b>110 x 110 x 25 mm</b>     |
| Light source                             | <b>LED</b>                   |
| Wattage                                  | <b>4 W</b>                   |
| Power supply                             | <b>220-240 V   50/60 Hz</b>  |
| Light source output                      | <b>368 lm</b>                |
| System output                            | <b>210 lm</b>                |
| System efficiency                        | <b>53 lm/W</b>               |
| Color Rendering Index – CRI              | <b>80</b>                    |
| LED energy class                         | <b>F</b>                     |
| LED lifetime                             | <b>L70 B50 &gt; 50.000 h</b> |
| Standard Deviation Color Matching (SDCM) | <b>MacAdam step 3</b>        |
| Electrical insulation class              | <b>Class I</b>               |
| IP rating                                | <b>IP 65</b>                 |
| Impact resistance rating                 | <b>IK 10 (20 joules)</b>     |
| Norms                                    | <b>EN 60598-1 +2-1</b>       |
| Weight                                   | <b>0.37 kg</b>               |
| Conformity                               | <b>CE UK CA</b>              |

## CODE OPTIONS



### FINISH

|           |                |
|-----------|----------------|
| <b>AG</b> | ALUMINIUM GREY |
| <b>AN</b> | ANTHRACITE     |
| <b>CO</b> | CORTEN         |
| <b>BR</b> | BRONZE         |
| <b>BI</b> | WHITE          |

### COLOUR TEMP.

|            |       |
|------------|-------|
| <b>27K</b> | 2700K |
| <b>3K</b>  | 3000K |
| <b>4K</b>  | 4000K |

ACCESSORIES



**STAMP** THE SERIES

