

Outdoor wall steplight luminaire

Minimum thickness for surface installation / Recessed installation flush with the wall using backbox optional accessory

Material: low copper content die-cast aluminium

UV resistant polycarbonate diffuser, recessed for an effective reduction of direct glare

Built-in phase-cut dimmable driver

Light source: LED unit

Rear cable entry / Spacer optional accessory for side cable entry / Through wiring allowed

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):



- D Dimmable version
- LV 24÷48V low voltage

Dimensions	175 x 175 x 30 mm
Light source	LED
Wattage	8 W
Power supply	220-240 V   50/60 Hz
Light source output	1077 lm
System output	520 lm
System efficiency	65 lm/W
Color Rendering Index – CRI	≥80
LED energy class	F
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	0.98 kg
Conformity	CE UK CA

**CODE OPTIONS**

FINISH		COLOUR TEMP.	
AG	ALUMINIUM GREY	27K	2700K
AN	ANTHRACITE	3K	3000K
CO	CORTEN	4K	4000K
BR	BRONZE		
BI	WHITE		

ACCESSORIES



**STAMP** THE SERIES

