

Pole complete with luminaire

Material: aluminium

UV resistant polycarbonate diffuser, recessed for an effective reduction of direct glare

Light source: mains voltage LED module, compatible with phase-cut dimmers

Supplied with H05RN-F pre-wired cable (optional waterproof connections to be ordered separately)

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):  
24V 24V low voltage


Dimensions	128 x 44 x H 600 mm
Light source	LED
Wattage	4 W
Power supply	220-240 V   50/60 Hz
Light source output	368 lm
System output	210 lm
System efficiency	53 lm/W
Color Rendering Index – CRI	80
LED energy class	F
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	2.2 kg
Conformity	CE UK CA

**CODE OPTIONS**

FINISH		COLOUR TEMP.	
<b>AG</b>	ALUMINIUM GREY	<b>27K</b>	2700K
<b>AN</b>	ANTHRACITE	<b>3K</b>	3000K
<b>CO</b>	CORTEN	<b>4K</b>	4000K
<b>BR</b>	BRONZE		


ACCESSORIES

STAMP POST  
ANCHOR PLATE L 128



5391

ACCESSORIES  
WATERPROOF CONNECTOR



1941

ACCESSORIES  
WATERPROOF CONNECTOR



1944

STAMP THE SERIES

