

Pole complete with luminaire

Material: aluminium

UV resistant polycarbonate diffuser, recessed for an effective reduction of direct glare

Light source: mains voltage LED module, compatible with phase-cut dimmers

Supplied with H05RN-F pre-wired cable (optional waterproof connections to be ordered separately)

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

**24V** 24V low voltage

Dimensions	<b>128 x 44 x H 600 mm</b>
Light source	<b>LED</b>
Wattage	<b>4 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
Light source output	<b>368 lm</b>
System output	<b>210 lm</b>
System efficiency	<b>53 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>F</b>
LED lifetime	<b>L70 B50 &gt; 50.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class I</b>
IP rating	<b>IP 65</b>
Impact resistance rating	<b>IK 10 (20 joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>2.2 kg</b>
Conformity	<b>CE UK CA</b>

## CODE OPTIONS

### FINISH


<b>AG</b>	ALUMINIUM GREY
<b>AN</b>	ANTHRACITE
<b>CO</b>	CORTEN
<b>BR</b>	BRONZE

### COLOUR TEMP.

<b>27K</b>	2700K
<b>3K</b>	3000K
<b>4K</b>	4000K


ACCESSORIES

STAMP POST  
ANCHOR PLATE L 128



5391

ACCESSORIES  
WATERPROOF CONNECTOR



1941

ACCESSORIES  
WATERPROOF CONNECTOR



1944

STAMP THE SERIES

