

Pole complete with luminaire

Material: aluminium

UV resistant polycarbonate diffuser, recessed for an effective reduction of direct glare

Light source: mains voltage LED module, compatible with phase-cut dimmers

Supplied with H05RN-F pre-wired cable (optional waterproof connections to be ordered separately)

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):
24V 24V low voltage


| | |
|--|----------------------|
| Dimensions | 128 x 44 x H 600 mm |
| Light source | LED |
| Wattage | 4 W |
| Power supply | 220-240 V 50/60 Hz |
| Light source output | 368 lm |
| System output | 210 lm |
| System efficiency | 53 lm/W |
| Color Rendering Index – CRI | 80 |
| LED energy class | F |
| LED lifetime | L70 B50 > 50.000 h |
| Standard Deviation Color Matching (SDCM) | MacAdam step 3 |
| Electrical insulation class | Class I |
| IP rating | IP 65 |
| Impact resistance rating | IK 10 (20 joules) |
| Norms | EN 60598-1 +2-1 |
| Weight | 2.2 kg |
| Conformity | CE UK CA |

CODE OPTIONS

| FINISH | | COLOUR TEMP. | |
|-----------|----------------|--------------|-------|
| AG | ALUMINIUM GREY | 27K | 2700K |
| AN | ANTHRACITE | 3K | 3000K |
| CO | CORTEN | 4K | 4000K |
| BR | BRONZE | | |


ACCESSORIES

STAMP POST
ANCHOR PLATE L 128



5391

ACCESSORIES
WATERPROOF CONNECTOR



1941

ACCESSORIES
WATERPROOF CONNECTOR



1944

STAMP THE SERIES

