



Pole complete with luminaire
 Material: aluminium
 UV resistant polycarbonate diffuser, recessed for an effective reduction of direct glare
 Built-in phase-cut dimmable driver
 Light source: LED unit
 Supplied with H05RN-F pre-wired cable (optional waterproof connections to be ordered separately)
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- S Version with sensor
- D Dimmable version
- LV 24÷48V low voltage

Dimensions	193 x 90 x H 600 mm
Light source	LED
Wattage	8 W
Power supply	220-240 V 50/60 Hz
Light source output	1077 lm
System output	520 lm
System efficiency	65 lm/W
Color Rendering Index – CRI	≥80
LED energy class	F
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	3.86 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH		COLOUR TEMP.	
AG	ALUMINIUM GREY	27K	2700K
AN	ANTHRACITE	3K	3000K
CO	CORTEN	4K	4000K
BR	BRONZE		

ACCESSORIES



STAMP THE SERIES

