

Pole complete with 2 luminaires

Material: aluminium

UV resistant polycarbonate diffuser, recessed for an effective reduction of direct glare

Built-in phase-cut dimmable drivers

Light source: LED unit

Supplied with two H05RN-F pre-wired cables (optional waterproof connections to be ordered separately)

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- S Version with sensor
- D Dimmable version
- LV 24÷48V low voltage


Dimensions	193 x 90 x H 900 mm
Light source	LED
Wattage	16 W
Power supply	220-240 V   50/60 Hz
Light source output	2154 lm
System output	1040 lm
System efficiency	65 lm/W
Color Rendering Index – CRI	≥80
LED energy class	F
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	6 kg
Conformity	CE UK CA

### CODE OPTIONS

FINISH		COLOUR TEMP.	
AG	ALUMINIUM GREY	27K	2700K
AN	ANTHRACITE	3K	3000K
CO	CORTEN	4K	4000K
BR	BRONZE		


ACCESSORIES

STAMP POST  
ANCHOR PLATE L 193



5392

ACCESSORIES  
WATERPROOF CONNECTOR



1941

ACCESSORIES  
WATERPROOF CONNECTOR



1944

**STAMP** THE SERIES

