

Pole complete with 2 luminaires

Material: aluminium

UV resistant polycarbonate diffuser, recessed for an effective reduction of direct glare

Built-in phase-cut dimmable drivers

Light source: LED unit

Supplied with two H05RN-F pre-wired cables (optional waterproof connections to be ordered separately)

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

**S** Version with sensor

**D** Dimmable version

**LV** 24÷48V low voltage

Dimensions	<b>193 x 90 x H 900 mm</b>
Light source	<b>LED</b>
Wattage	<b>16 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
Light source output	<b>2154 lm</b>
System output	<b>1040 lm</b>
System efficiency	<b>65 lm/W</b>
Color Rendering Index – CRI	<b>≥80</b>
LED energy class	<b>F</b>
LED lifetime	<b>L70 B50 &gt; 50.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class I</b>
IP rating	<b>IP 65</b>
Impact resistance rating	<b>IK 10 (20 joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>6 kg</b>
Conformity	<b>CE UK CA</b>

## CODE OPTIONS

### FINISH


**AG** ALUMINIUM GREY  
**AN** ANTHRACITE  
**CO** CORTEN  
**BR** BRONZE

### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K


ACCESSORIES

STAMP POST  
ANCHOR PLATE L 193



5392

ACCESSORIES  
WATERPROOF CONNECTOR



1941

ACCESSORIES  
WATERPROOF CONNECTOR



1944

**STAMP** THE SERIES

