



Outdoor spotlight for wall, stem and ground installation

Adjustable luminaire with stable fastening in the chosen point

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass, sealed to the frame

Light source: mains voltage LED module, compatible with phase-cut dimmers

The spotlight is hermetically sealed with a two-component resin and supplied with a 1,5 m H05RN-F buriable cable. The cable can pass through a special hole in the base of the arm

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

24V 24V low voltage

MT7 7 m cable length

Dimensions	Ø 80 x H 96 x 36 mm
Light source	LED
Wattage	4 W
Power supply	220-240 V 50/60 Hz
Light source output	384 lm
System output	290 lm
System efficiency	73 lm/W
Color Rendering Index – CRI	80
LED energy class	F
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 67
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	0.44 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG	ALUMINIUM GREY
AN	ANTHRACITE
BR	BRONZE
VE	GREEN

on request:

CO	CORTEN
BI	WHITE

COLOUR TEMP.

27K	2700K
3K	3000K
4K	4000K

OPTIC

standard	40°
optional optics	
12	12°
90	90°

ACCESSORIES

<p>CLOCK STEM H 600</p>  <p>4693</p>	<p>CLOCK STEM H 1200</p>  <p>4694</p>	<p>CLOCK STEM H 2300</p>  <p>4699</p>	<p>ACCESSORIES WATERPROOF CONNECTOR</p>  <p>1941</p>
<p>ACCESSORIES WATERPROOF CONNECTOR</p>  <p>1944</p>	<p>ACCESSORIES WATERPROOF CONNECTOR</p>  <p>1942</p>	<p>CLOCK 80 SHIELD</p>  <p>4668</p>	<p>CLOCK STEM JOINT</p>  <p>4695</p>
<p>CLOCK SPIKE</p>  <p>4691</p>	<p>CLOCK WALL ARM 380</p>  <p>4692</p>	<p>CLOCK STEM WALL SUPPORT</p>  <p>4681</p>	<p>CLOCK STEM WALL 900</p>  <p>4682</p>
<p>CLOCK STEM WALL 1800</p>  <p>4683</p>	<p>CLOCK STRAP</p>  <p>1602</p>	<p>CLOCK WALL ARM 680</p>  <p>4690</p>	

CLOCK THE SERIES

