



Outdoor spotlight for wall, stem and ground installation

Adjustable luminaire with stable fastening in the chosen point

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass, sealed to the frame

Light source: mains voltage LED module, compatible with phase-cut dimmers

The spotlight is hermetically sealed with a two-component resin and supplied with a 1,5 m H05RN-F buriable cable. The cable can pass through a special hole in the base of the arm

Finish with double painting after anti-corrosion treatments: epoxy-based primer and polyester powder coating

On request versions (additional code):

**24V** 24V low voltage

**MT7** 7 m cable length

Dimensions	Ø 80 x H 96 x 36 mm
Light Source	LED
Power	4 W
Voltage/Frequency	220-240 V   50/60 Hz
Light output source	384 lm
LUMEN OUTPUT	290 lm
System efficiency	72 lm/W
Color Rendering Index – CRI	≥80
LED energy class	F
Electrical insulation class	Class I
IP rating	IP 67
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	0.44 kg
Certifications	CE UK CA

## CODE OPTIONS

### FINISH

<b>AG</b>	ALUMINIUM GREY
<b>AN</b>	ANTHRACITE
<b>BR</b>	BRONZE
<b>VE</b>	GREEN

on request:

<b>CO</b>	CORTEN
<b>BI</b>	WHITE

### COLOUR TEMP.

<b>27K</b>	2700K
<b>3K</b>	3000K
<b>4K</b>	4000K

### OPTIC

**standard** 40°

optional optics

<b>12</b>	12°
<b>90</b>	90°

CLOCK Ø 80 LED 4W  
4661



CLOCK THE SERIES

