

Outdoor spotlight for wall, stem and ground installation

Adjustable luminaire with stable fastening in the chosen point

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass, sealed to the frame

External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: 3 RGBW LEDs and a device to receive DMX standard 512 signal sent from the control unit 1181 or another compatible unit. The contained light source is intended for use in applications requiring high-quality coloured light

Supplied with 0,5 m cable: signal + 24V

Up to 32 luminaires can be connected to each control unit

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

Dimensions	Ø 120 x H 136 x 36 mm
Light source	LED RGBW
Light source info	max
Wattage	25 W
Power supply	24 Vdc
Light source output	990 lm
System output	690 lm
System efficiency	28 lm/W
Electrical insulation class	Class III
IP rating	IP 67
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	0.72 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
AN ANTHRACITE
BR BRONZE
VE GREEN

on request:

CO CORTEN
BI WHITE













OPTIC

standard 30°

optional optics

10 10°
54 54°

ACCESSORIES

<p>CLOCK STEM H 600</p>  <p>4693</p>	<p>CLOCK STEM H 1200</p>  <p>4694</p>	<p>CLOCK STEM H 2300</p>  <p>4699</p>	<p>CLOCK 120 SHIELD</p>  <p>4669</p>
<p>CLOCK STEM JOINT</p>  <p>4695</p>	<p>CLOCK SPIKE</p>  <p>4691</p>	<p>CLOCK WALL ARM 380</p>  <p>4692</p>	<p>CLOCK STEM WALL SUPPORT</p>  <p>4681</p>
<p>CLOCK STEM WALL 900</p> <p>4682</p>	<p>CLOCK STEM WALL 1800</p> <p>4683</p>	<p>ACCESSORIES SIGNAL GENERATOR</p>  <p>1181</p>	<p>ACCESSORIES 24V DRIVER - 24W</p>  <p>1924</p>
<p>ACCESSORIES 24V DRIVER - 60W</p>  <p>1925</p>	<p>ACCESSORIES 24V DRIVER - 150W</p>  <p>1926</p>		

RGBW THE SERIES

