

Outdoor spotlight for wall, stem and ground installation

Adjustable luminaire with stable fastening in the chosen point

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass, sealed to the frame

External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: 3 RGBW LEDs and a device to receive DMX standard 512 signal sent from the control unit 1181 or another compatible unit. The contained light source is intended for use in applications requiring high-quality coloured light

Supplied with 0,5 m cable: signal + 24V

Up to 32 luminaires can be connected to each control unit

Finish with double painting after anti-corrosion treatments: epoxy-based primer and polyester powder coating

|                             |                       |
|-----------------------------|-----------------------|
| Dimensions                  | Ø 120 x H 136 x 36 mm |
| Light Source                | LED RGBW              |
| Extra info W                | max                   |
| Power                       | 25 W                  |
| Voltage/Frequency           | 24V DC                |
| Light output source         | 990 lm                |
| LUMEN OUTPUT                | 690 lm                |
| System efficiency           | 28 lm/W               |
| Electrical insulation class | Class III             |
| IP rating                   | IP 67                 |
| Impact resistance rating    | IK 08 (5 Joules)      |
| Norms                       | EN 60598-1 +2-1       |
| Weight                      | 0.72 kg               |
| Certifications              | CE UK CA              |

## CODE OPTIONS

### FINISH

|    |                |
|----|----------------|
| AG | ALUMINIUM GREY |
| AN | ANTHRACITE     |
| BR | BRONZE         |
| VE | GREEN          |












on request:

|    |        |
|----|--------|
| CO | CORTEN |
| BI | WHITE  |

### OPTIC

|                 |     |
|-----------------|-----|
| standard        | 30° |
| optional optics |     |
| 10              | 10° |
| 54              | 54° |

ACCESSORIES

|   |   |   |   |
|---|---|---|---|
| <p>CLOCK<br/>STEM H 600</p>  <p>4693</p>               | <p>CLOCK<br/>STEM H 1200</p>  <p>4694</p>        | <p>CLOCK<br/>STEM H 2300</p>  <p>4699</p>              | <p>CLOCK<br/>Ø 120 SHIELD</p>  <p>4669</p>             |
| <p>CLOCK<br/>JOINT</p>  <p>4695</p>                    | <p>CLOCK<br/>SPIKE</p>  <p>4691</p>              | <p>CLOCK<br/>WALL ARM L 380</p>  <p>4692</p>           | <p>CLOCK<br/>WALL SUPPORT</p>  <p>4681</p>             |
| <p>CLOCK<br/>WALL STEM L 900</p>  <p>4682</p>        | <p>CLOCK<br/>WALL STEM L 1800</p>  <p>4683</p> | <p>ACCESSORIES<br/>24V CONTROL GEAR</p>  <p>1924</p> | <p>ACCESSORIES<br/>24V CONTROL GEAR</p>  <p>1925</p> |
| <p>ACCESSORIES<br/>24V CONTROL GEAR</p>  <p>1926</p> |   |   |   |

RGBW

THE SERIES

