



Outdoor luminaire for pole installation

The Ø 150 version is recommended for 375 mm high pole (code 3421)

Material: upper part and body in low copper content die-cast aluminium / Anti-glare aluminium internal cone

Diffuser: clear satin polycarbonate

Light source: mains voltage LED module, compatible with phase-cut dimmers

Equipped with two M16 cable glands to allow through wiring

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

**24V** 24V low voltage

Dimensions	Ø 152 x H 111 mm
Light source	LED
Wattage	10 W
Power supply	220-240 V   50/60 Hz
Light source output	1200 lm
System output	863 lm
System efficiency	86 lm/W
Color Rendering Index – CRI	80
LED energy class	E (4000K), F (2700K), F (3000K)
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	0.54 kg
Conformity	CE UK CA

## CODE OPTIONS

### FINISH

**AN** ANTHRACITE

on request:

**AG** ALUMINIUM GREY

**CO** CORTEN

**BR** BRONZE

### COLOUR TEMP.

**27K** 2700K

**3K** 3000K

**4K** 4000K

ACCESSORIES

ACCESSORIES  
ADAPTOR



5506

ACCESSORIES  
POLE H 375



3421

ACCESSORIES  
POLE H 800



3422

ACCESSORIES  
ANCHOR PLATE



5519

CANTHARELLUS

THE SERIES

