

Outdoor luminaire for pole installation

It can be installed on Goccia Illuminazione Ø 76 mm dedicated steel poles or on standard Ø 60 mm metal poles

Material: low copper content die-cast aluminium

UV resistant polycarbonate diffuser and opalized lenticular screen for maximum visual comfort

Built-in driver

Light source: LED unit

Easier wiring to the inspection door thanks to the 2x1 cable, 2,80 m long; further M16 cable gland for additional wiring

Optional surge protection device (SPD) to be ordered separately

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D Dimmable version

Dimensions	Ø 360 x H 327 mm
Light source	LED
Wattage	43 W
Power supply	220-240 V 50/60 Hz
Light source output	6400 lm
System output	3658 lm
System efficiency	85 lm/W
Color Rendering Index – CRI	80
LED energy class	D
LED lifetime	L80 B20 > 80.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	4.54 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AN ANTHRACITE

on request:

AG ALUMINIUM GREY

COLOUR TEMP.

27K 2700K

3K 3000K

4K 4000K


ACCESSORIES

ACCESSORIES
SPD



1966

ACCESSORIES
POLE H 2500 – BURIABLE




3504

ACCESSORIES
POLE H 3000 – BURIABLE



3505

ACCESSORIES
POLE H 3500 – BURIABLE



3506

CANTHUS

THE SERIES

