



Outdoor luminaire for wall installation

Material: extruded aluminium striated housing / Glass holding frames and box to fix to wall in low copper content die-cast aluminium

Diffuser: milled and tempered transparent glass, flush with the structure

Built-in driver

Light source: LED unit / Adjustable optics $\pm 10^\circ$

Optional plug/socket connector for 3x2,5 mm² cables to be ordered separately (code 1943)

Stainless steel Allen screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- E Emergency

Dimensions	Ø 120 x H 441 x 175 mm
Light source	LED
Multiple sources	2x
Wattage	36 W
Power supply	220-240 V 50/60 Hz
Light source output	4872 lm
System output	4000 lm
System efficiency	111 lm/W
Color Rendering Index – CRI	80
LED energy class	E
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	3.88 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

- AG** ALUMINIUM GREY
- AN** ANTHRACITE

COLOUR TEMP.

- 27K** 2700K
- 3K** 3000K
- 4K** 4000K

OPTIC

- standard** 18°
- optional optics
- 50** 50°
- 90** 90°

ACCESSORIES



CORINTHIA THE SERIES

