



Outdoor luminaire for wall installation

Material: extruded aluminium striated housing / Glass holding frames and box to fix to wall in low copper content die-cast aluminium

Diffuser: milled and tempered transparent glass, flush with the structure

Built-in driver

Light source: LED unit / Adjustable optics  $\pm 10^\circ$

Optional plug/socket connector for 3x2,5 mm<sup>2</sup> cables to be ordered separately (code 1943)

Stainless steel Allen screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- E Emergency

Dimensions	<b>Ø 120 x H 441 x 175 mm</b>
Light source	<b>LED</b>
Wattage	<b>18 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
Light source output	<b>2643 lm</b>
System output	<b>2000 lm</b>
System efficiency	<b>111 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>E</b>
LED lifetime	<b>L80 B10 86.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class II</b>
IP rating	<b>IP 65</b>
Impact resistance rating	<b>IK 08 (5 Joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>3.88 kg</b>
Conformity	<b>CE UK CA</b>

**CODE OPTIONS**

**FINISH**

- AG** ALUMINIUM GREY
- AN** ANTHRACITE

**COLOUR TEMP.**

- 27K** 2700K
- 3K** 3000K
- 4K** 4000K

**OPTIC**

- standard** 18°
- optional optics
- 50** 50°
- 90** 90°

ACCESSORIES



**CORINTHIA** THE SERIES

