



Outdoor luminaire for wall installation

Material: extruded aluminium striated housing / Glass holding frames and box to fix to wall in low copper content die-cast aluminium

Diffuser: milled and tempered transparent glass, flush with the structure

Built-in driver

Light source: LED unit / Adjustable optics $\pm 10^\circ$

Optional plug/socket connector for 3x2,5 mm² cables to be ordered separately (code 1943)

Stainless steel Allen screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- E Emergency

| | |
|--|-------------------------------|
| Dimensions | Ø 120 x H 441 x 175 mm |
| Light source | LED |
| Wattage | 18 W |
| Power supply | 220-240 V 50/60 Hz |
| Light source output | 2643 lm |
| System output | 2000 lm |
| System efficiency | 111 lm/W |
| Color Rendering Index – CRI | 80 |
| LED energy class | E |
| LED lifetime | L80 B10 86.000 h |
| Standard Deviation Color Matching (SDCM) | MacAdam step 3 |
| Electrical insulation class | Class II |
| IP rating | IP 65 |
| Impact resistance rating | IK 08 (5 Joules) |
| Norms | EN 60598-1 +2-1 |
| Weight | 3.88 kg |
| Conformity | CE UK ENEC |

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
AN ANTHRACITE

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

OPTIC

standard 18°
optional optics
50 50°
90 90°

ACCESSORIES



CORINTHIA THE SERIES

