



Outdoor luminaire for wall/ceiling installation

Material: housing and base in low copper content die-cast aluminium / Aluminium internal plate

Diffuser: UV resistant opal polycarbonate / Silicone sealing gasket

Built-in driver

Light source: LED unit

Rear cable entry

Stainless steel screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

**D** Dimmable version

Dimensions	<b>Ø 268 x 118 mm</b>
Light source	<b>LED</b>
Wattage	<b>15 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
Light source output	<b>2300 lm</b>
System output	<b>600 lm</b>
System efficiency	<b>40 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>C</b>
LED lifetime	<b>L70 B50 72.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class I</b>
IP rating	<b>IP 66</b>
Impact resistance rating	<b>IK 10 (20 joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>1.36 kg</b>
Conformity	<b>CE UK CA</b>

**CODE OPTIONS**

**FINISH**

**AG** ALUMINIUM GREY  
**AN** ANTHRACITE  
**BI** WHITE

**COLOUR TEMP.**

**27K** 2700K  
**3K** 3000K  
**4K** 4000K