



Outdoor luminaire for wall/ceiling installation
 Material: AISI 316L stainless steel housing / Die-cast aluminium base / Aluminium internal plate
 Diffuser: UV resistant opal polycarbonate / Silicone sealing gasket
 Built-in driver
 Light source: LED unit
 Rear cable entry
 Stainless steel screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):
 D Dimmable version

| | |
|--|----------------------|
| Dimensions | Ø 268 x 118 mm |
| Light source | LED |
| Wattage | 15 W |
| Power supply | 220-240 V 50/60 Hz |
| Light source output | 2300 lm |
| System output | 600 lm |
| System efficiency | 40 lm/W |
| Color Rendering Index – CRI | 80 |
| LED energy class | C |
| LED lifetime | L70 B50 72.000 h |
| Standard Deviation Color Matching (SDCM) | MacAdam step 3 |
| Electrical insulation class | Class I |
| IP rating | IP 66 |
| Impact resistance rating | IK 10 (20 joules) |
| Norms | EN 60598-1 +2-1 |
| Weight | 1.63 kg |
| Conformity | CE UK CA |

CODE OPTIONS

| FINISH | COLOUR TEMP. |
|--------------------|--------------|
| IN STAINLESS STEEL | 27K 2700K |
| | 3K 3000K |
| | 4K 4000K |