

Outdoor luminaire for pole/wall installation

It can be installed on Goccia Illuminazione poles or on any standard Ø 60 mm pole

Material: lamp housing with die-cast aluminium spoked support / Self-extinguishing technopolymer wiring box

Diffuser: clear polycarbonate

Light source: mains voltage LED module, compatible with phase-cut dimmers

Equipped with two M16 cable glands to allow through wiring

Dimensions	Ø 382 x H 418 mm
Light source	LED
Wattage	10 W
Power supply	220-240 V   50/60 Hz
Light source output	1125 lm
System output	521 lm
System efficiency	52 lm/W
Color Rendering Index – CRI	≥80
LED energy class	E (4000K), F (2700K), F (3000K)
LED lifetime	L70 B10 45.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Norms	EN 60598-1 +2-1
Weight	0.92 kg
Conformity	CE UK CA

## CODE OPTIONS

### FINISH

**AN** ANTHRACITE

on request:

**CO** CORTEN

**BR** BRONZE

### COLOUR TEMP.

**27K** 2700K



**3K** 3000K

**4K** 4000K

COMPONENTS



ACCESSORIES



I-DEA THE SERIES

