



Outdoor luminaire for pole/wall installation

It can be installed on Goccia Illuminazione poles or on any standard Ø 60 mm pole

The internal anti-dazzling grid can be adjusted using the outer lever to shield light to prevent glare

Material: body complete with self-extinguishing technopolymer wiring box / Painted aluminium connection ring

Diffuser: UV resistant clear polycarbonate

Ballast inside

Luminaire supplied without light source

Equipped with two M16 cable glands to allow through wiring

Dimensions	Ø 60 x H 415 x H 235 mm
Wattage	11 W
Power supply	230 V   50 Hz
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 09 (10 Joules)
Norms	EN 60598-1 +2-1
Weight	0.8 kg
Conformity	CE UK CA

## CODE OPTIONS

### FINISH

**AN** ANTHRACITE

on request:

**CO** CORTEN

**BR** BRONZE

# I-LUX aluminium + anti-dazzling grid G23 11W

## 5502

### ACCESSORIES

ACCESSORIES  
SPIKE



5505

ACCESSORIES  
ADAPTOR



5506

I-LUX  
ALUMINIUM SINGLE WALL  
ARM



5513

I-LUX  
ALUMINIUM DOUBLE WALL  
ARM



5514

ACCESSORIES  
POLE H 375



3421

ACCESSORIES  
POLE H 800



3422

ACCESSORIES  
ANCHOR PLATE



5519

### I-LUX THE SERIES

