



Outdoor luminaire for pole/wall installation

It can be installed on Goccia Illuminazione poles or on any standard Ø 60 mm pole

The internal anti-dazzling grid can be adjusted using the outer lever to shield light to prevent glare

Material: body complete with self-extinguishing technopolymer wiring box / Chromed connection ring

Diffuser: UV resistant clear polycarbonate

Ballast inside

Luminaire supplied without light source

Equipped with two M16 cable glands to allow through wiring

Dimensions	Ø 60 x H 415 x H 235 mm
Wattage	11 W
Power supply	230 V 50 Hz
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 09 (10 Joules)
Norms	EN 60598-1 +2-1
Weight	1.1 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

IN STAINLESS STEEL

I-LUX stainless steel + anti-dazzling grid G23 11W

5504

ACCESSORIES

ACCESSORIES
STAINLESS STEEL POLE H 375



3511

ACCESSORIES
STAINLESS STEEL POLE H 800



3512

ACCESSORIES
SPIKE



5505

ACCESSORIES
ADAPTOR



5506

I-LUX
STAINLESS STEEL - SINGLE
WALL ARM



5512

I-LUX
STAINLESS STEEL - DOUBLE
WALL ARM



5516

ACCESSORIES
ANCHOR PLATE



5519

I-LUX THE SERIES

