



Outdoor luminaire for pole/wall installation

It can be installed on Goccia Illuminazione poles or on any standard Ø 60 mm pole

Material: body complete with self-extinguishing technopolymer wiring box / Satin aluminium internal parts / Painted aluminium connection ring

Diffuser: UV resistant opal polycarbonate

Built-in driver

Luminaire supplied with LED G23 light source

Equipped with two M16 cable glands to allow through wiring

Dimensions	Ø 60 x H 440 x H 260 mm
Light source	LED
Wattage	9 W
Power supply	220-240 V   50/60 Hz
Light source output	930 lm
System output	600 lm
System efficiency	67 lm/W
Color Rendering Index – CRI	≥80
LED energy class	F
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 09 (10 Joules)
Norms	EN 60598-1 +2-1
Weight	0.4 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH		COLOUR TEMP.	
<b>AN</b>	ANTHRACITE	<b>27K</b>	2700K
		<b>3K</b>	3000K
	on request:	<b>4K</b>	4000K
<b>CO</b>	CORTEN		
<b>BR</b>	BRONZE		

**I-LUX aluminium** LED G23 9W

**5517**

ACCESSORIES

ACCESSORIES  
SPIKE



**5505**

ACCESSORIES  
ADAPTOR



**5506**

I-LUX  
ALUMINIUM SINGLE WALL  
ARM



**5513**

I-LUX  
ALUMINIUM DOUBLE WALL  
ARM



**5514**

ACCESSORIES  
POLE H 375



**3421**

ACCESSORIES  
POLE H 800



**3422**

ACCESSORIES  
ANCHOR PLATE



**5519**

**I-LUX** THE SERIES

