

Outdoor luminaire for pole/wall installation

It can be installed on Goccia Illuminazione poles or on any standard Ø 60 mm pole

Material: body complete with self-extinguishing technopolymer wiring box / Satin aluminium internal parts / Chromed connection ring

Diffuser: UV resistant opal polycarbonate

Built-in driver

Luminaire supplied with LED G23 light source

Equipped with two M16 cable glands to allow through wiring

Dimensions	Ø 60 x H 440 x H 260 mm
Light source	LED
Wattage	9 W
Power supply	220-240 V   50/60 Hz
Light source output	930 lm
System output	600 lm
System efficiency	67 lm/W
Color Rendering Index – CRI	≥80
LED energy class	F
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 09 (10 Joules)
Norms	EN 60598-1 +2-1
Weight	0.7 kg
Conformity	CE UK CA

CODE OPTIONS


FINISH		COLOUR TEMP.	
IN	STAINLESS STEEL	27K	2700K
		3K	3000K
		4K	4000K

**I-LUX stainless steel** LED G23 9W

**5540**


ACCESSORIES

ACCESSORIES  
STAINLESS STEEL POLE H 375




**3511**

ACCESSORIES  
STAINLESS STEEL POLE H 800




**3512**

ACCESSORIES  
SPIKE



**5505**

ACCESSORIES  
ADAPTOR



**5506**

I-LUX  
STAINLESS STEEL - SINGLE  
WALL ARM




**5512**

I-LUX  
STAINLESS STEEL - DOUBLE  
WALL ARM



**5516**

ACCESSORIES  
ANCHOR PLATE



**5519**

**I-LUX** THE SERIES

