

Outdoor luminaire for pole installation

It can be installed on Goccia Illuminazione poles or on any standard Ø 60 mm pole

Material: body complete with self-extinguishing technopolymer wiring box / Satin aluminium internal parts / Chromed connection ring

Diffuser: UV resistant clear polycarbonate

Built-in driver

Light source: LED unit

Equipped with two M16 cable glands to allow through wiring

On request versions (additional code):

LV 10÷52V low voltage

Dimensions	Ø 60 x H 415 x H 235 mm
Light source	LED
Wattage	7.5 W
Power supply	100-240 V 50/60 Hz
Light source output	731 lm
System output	380 lm
System efficiency	51 lm/W
Color Rendering Index – CRI	80
LED energy class	C
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 09 (10 Joules)
Norms	EN 60598-1 +2-1
Weight	0.59 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

IN STAINLESS STEEL

COLOUR TEMP.

3K 3000K
4K 4000K

I-MAGO STAINLESS STEEL LED 7.5W

5500


ACCESSORIES

ACCESSORIES
STAINLESS STEEL POLE H 375



3511

ACCESSORIES
STAINLESS STEEL POLE H 800



3512

ACCESSORIES
SPIKE



5505

ACCESSORIES
ADAPTOR



5506

ACCESSORIES
ANCHOR PLATE



5519

I-MAGO THE SERIES

