

Outdoor luminaire for pole installation

It can be installed on Goccia Illuminazione poles or on any standard Ø 60 mm pole

Material: low copper content die-cast aluminium

Built-in driver

Light source: shielded LED unit inside the diffuser

Equipped with two M16 cable glands to allow through wiring

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

LV 12-24V low voltage

Dimensions	Ø 60 x H 230 mm
Light source	LED
Wattage	4.6 W
Power supply	100-240 V   50/60 Hz
Light source output	470 lm
System output	115 lm
System efficiency	25 lm/W
Color Rendering Index – CRI	80
LED energy class	E (3000K), E (4000K), F (2700K)
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	0.77 kg
Conformity	CE UK CA

## CODE OPTIONS

### FINISH

**AG** ALUMINIUM GREY  
**AN** ANTHRACITE  
**BR** BRONZE

### COLOUR TEMP.



**27K** 2700K  
**3K** 3000K  
**4K** 4000K

on request:

**CO** CORTEN



COMPONENTS



ACCESSORIES

