


IANUS 120 H 600 1x LED 8W

7073







Pole for garden and urban lighting

Material: low copper content die-cast aluminium

Photo-etched opal polycarbonate lenticular diffuser for a wide and uniform light distribution

Built-in driver

Light source: LED unit

Watertight wiring through the supplied cable that powers the integrated driver. Further M16 entry for additional wiring, positioned in the lower part of the closing cap in technopolymer

Color matching side fixing screws in stainless steel

Finish with double painting after anti-corrosion treatments: epoxy-based primer and polyester powder coating

On request versions (additional code):

D Dimmable version

LV 24÷48V low voltage

Dimensions	Ø 120 x H 600 mm		
Light Source	LED		
Power	8 W		
Voltage/Frequency	100-240 V 50/60 Hz		
Light output source	951 lm		
LUMEN OUTPUT	515 lm		
System efficiency	64 lm/W		
Color Rendering Index - CRI	80		
LED energy class	E		
Electrical insulation class	Class I		
IP rating	IP 66		
Impact resistance rating	IK 10 (20 joules)		
Norms	EN 60598-1 +2-1		
Weight	5.54 kg		
Certifications	C€ FR		

CODE OPTIONS

on request:

СО

FINISH		COLOUR TEMP.		OPTIC	
AG AN BR	ALUMINIUM GREY ANTHRACITE BRONZE	27K 3K 4K	2700K 3000K 4000K	standard	DIFFUSE



CORTEN





IANUS 120 H 600 1x LED 8W

7073

ACCESSORIES



IANUS

THE SERIES









