


IANUS 120 H 600 1x LED 8W

7073



Pole for garden and urban lighting

Material: low copper content die-cast aluminium

Photo-etched opal polycarbonate lenticular diffuser for a wide and uniform light distribution

Built-in driver

Light source: LED unit

Watertight wiring through the supplied cable that powers the integrated driver. Further M16 entry for additional wiring, positioned in the lower part of the closing cap in technopolymer

Color matching side fixing screws in stainless steel

Finish with double painting after anti-corrosion treatments: epoxy-based primer and polyester powder coating

On request versions (additional code):

D Dimmable version

LV 24÷48V low voltage

Dimensions	Ø 120 x H 600 mm
Light Source	LED
Power	8 W
Voltage/Frequency	100-240 V 50/60 Hz
Light output source	951 lm
LUMEN OUTPUT	515 lm
System efficiency	64 lm/W
Color Rendering Index – CRI	80
LED energy class	E
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	5.54 kg
Certifications	CE UK CA

CODE OPTIONS

FINISH

AG	ALUMINIUM GREY
AN	ANTHRACITE
BR	BRONZE

COLOUR TEMP.

27K	2700K
3K	3000K
4K	4000K

OPTIC

standard	DIFFUSE
-----------------	---------

on request:


CO	CORTEN
-----------	--------

IANUS 120 H 600 1x LED 8W

7073



ACCESSORIES



IANUS

THE SERIES

