

Pole for garden and urban lighting

Material: low copper content die-cast aluminium

Photo-etched opal polycarbonate lenticular diffuser for a wide and uniform light distribution

Built-in driver

Light source: LED unit

Watertight wiring through the supplied cable that powers the integrated driver. Further M16 cable gland for additional wiring, positioned in the lower part of the closing cap in technopolymer

Color matching side fixing screws in stainless steel

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- LV 24÷48V low voltage

Dimensions	Ø 120 x H 1000 mm
Light source	LED
Wattage	8 W
Power supply	100-240 V   50/60 Hz
Light source output	951 lm
System output	515 lm
System efficiency	64 lm/W
Color Rendering Index – CRI	80
LED energy class	E
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	7.36 kg
Conformity	CE UK CA

## CODE OPTIONS

### FINISH

- AG ALUMINIUM GREY
- AN ANTHRACITE
- BR BRONZE


### COLOUR TEMP.

- 27K 2700K
- 3K 3000K
- 4K 4000K

on request:

- CO CORTEN

ACCESSORIES



IANUS THE SERIES

