



Urban lighting pole complete with luminaire
 Equipped with buriable anchoring unit
 Material: Ø 120 mm luminaire in low copper content die-cast aluminium coupled in continuity with extruded aluminum pole
 Photo-etched polycarbonate lenticular diffuser
 Built-in driver
 Light source: recessed LED unit to house dedicated optics
 Watertight wiring through the supplied cable that powers the integrated driver. Further M16 cable gland for additional wiring, positioned in the lower part of the closing cap in technopolymer
 Color matching side fixing screws in stainless steel
 Optional surge protection device (SPD) to be ordered separately
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- D6 Virtual midnight

Dimensions	Ø 120 x H 2400 mm
Light source	LED
Wattage	16 W
Power supply	220-240 V 50/60 Hz
Light source output	1952 lm
System output	934 lm
System efficiency	58 lm/W
Color Rendering Index – CRI	80
LED energy class	E (3000K), E (4000K), F (2700K)
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	16 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

- AG ALUMINIUM GREY
- AN ANTHRACITE
- BR BRONZE

on request:

- CO CORTEN

COLOUR TEMP.

- 27K 2700K
- 3K 3000K
- 4K 4000K

OPTIC

standard DIFFUSE

optional optics

- N ASYMMETRIC NARROW
- W ASYMMETRIC WIDE

ACCESSORIES



IANUS THE SERIES

