


IANUS URBAN 2x - BURIABLE LED 32W 7082







Urban lighting pole

Complete with buriable anchoring unit

Material: Ø 120 mm luminaire in low copper content die-cast aluminium coupled in continuity with extruded aluminum pole

Photo-etched polycarbonate lenticular diffuser

Built-in driver

Light source: recessed LED unit to house dedicated optics

Watertight wiring through the supplied cable that powers the integrated driver. Further M16 entry for additional wiring, positioned in the lower part of the closing cap in technopolymer

Color matching side fixing screws in stainless steel

Optional surge protection device (SPD) to be ordered separately (codes 1965-1966)

Finish with double painting after anti-corrosion treatments: epoxy-based primer and polyester powder coating

On request versions (additional code):

D Dimmable version

D6 Virtual midnight

Dimensions	Ø 120 x H 2400 mm
Light Source	LED
Multiple Sources	2x
Power	32 W
Voltage/Frequency	220-240 V 50/60 Hz
Light output source	3904 lm
LUMEN OUTPUT	1868 lm
System efficiency	58 lm/W
Color Rendering Index - CRI	80
LED energy class	E (3000K), E (4000K), F (2700K)
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	15.5 kg
Certifications	C€ F¥

CODE OPTIONS

FINIS	Н	COLOU	JR TEMP.	OPTIC		
AG	ALUMINIUM GREY	27K	2700K	standard	DIFFUSE	
AN BR	ANTHRACITE BRONZE	3K 4K	3000K 4000K	optional op	optional optics	
on request:		N W	ASYMMETRIC NARROW ASYMMETRIC WIDE			
СО	CORTEN				NOTIVINETITIO VIDE	









IANUS URBAN 2x - BURIABLE LED 32W 7082



ACCESSORIES



IANUS

THE SERIES







