

Outdoor luminaire for wall/ceiling installation  
 Material: UV resistant polycarbonate  
 Diffuser: moulded opal glass / Silicone sealing gasket  
 Light source: mains voltage LED module, compatible with phase-cut dimmers  
 Rear or side cable entry by means of gland or conduit / Through wiring allowed  
 Finish: UV resistant spray painting with polyurethane resins



On request versions (additional code):  
**S** Version with sensor

Dimensions	<b>300 x 207 x 91 mm</b>
Light source	<b>LED</b>
Wattage	<b>10 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
Light source output	<b>1125 lm</b>
System output	<b>592 lm</b>
System efficiency	<b>59 lm/W</b>
Color Rendering Index – CRI	<b>≥80</b>
LED energy class	<b>E (4000K), F (2700K), F (3000K)</b>
LED lifetime	<b>L70 B10 45.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class II</b>
IP rating	<b>IP 65</b>
Impact resistance rating	<b>IK 08 (5 Joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>1.37 kg</b>
Conformity	<b>CE UK CA</b>

**CODE OPTIONS**

FINISH		COLOUR TEMP.	
<b>NE</b>	BLACK	<b>27K</b>	2700K
		<b>3K</b>	3000K
		<b>4K</b>	4000K

COMPONENTS



**JACK** THE SERIES

