

Outdoor luminaire for wall/ceiling installation

Material: UV resistant polycarbonate

Diffuser: UV resistant opal polycarbonate / Silicone sealing gasket

Light source: mains voltage LED module, compatible with phase-cut dimmers

Rear or side cable entry by means of gland or conduit / Through wiring allowed

Finish: UV resistant spray painting with polyurethane resins

On request versions (additional code):

- S Version with sensor
- D Dimmable version

Dimensions	Ø 274 x 109 mm
Light source	LED
Wattage	10 W
Power supply	220-240 V 50/60 Hz
Light source output	1125 lm
System output	552 lm
System efficiency	55 lm/W
Color Rendering Index – CRI	≥80
LED energy class	E (4000K), F (2700K), F (3000K)
LED lifetime	L70 B10 45.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	1.55 kg
Conformity	CE UK CA

CODE OPTIONS






FINISH

NE BLACK

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

COMPONENTS



JACK THE SERIES

