



Outdoor luminaire for wall installation  
 Completely matt black inside to avoid any unwanted flare  
 Material: low copper content die-cast aluminium  
 Diffuser: ultra-white transparent tempered glass  
 Built-in driver  
 Light source: LED unit  
 Rear cable entry  
 Color matching stainless steel Allen screws  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D Dimmable version

Dimensions	<b>160 x 160 x 182 mm</b>
Light source	<b>LED</b>
Wattage	<b>6.4 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
Light source output	<b>640 lm</b>
System output	<b>168 lm</b>
System efficiency	<b>26 lm/W</b>
Color Rendering Index – CRI	<b>85</b>
LED energy class	<b>F</b>
Electrical insulation class	<b>Class II</b>
IP rating	<b>IP 65</b>
Impact resistance rating	<b>IK 08 (5 Joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>4.2 kg</b>
Conformity	<b>CE UK CA</b>

## CODE OPTIONS

FINISH		COLOUR TEMP.	
<b>AG</b>	ALUMINIUM GREY	<b>3K</b>	3000K
<b>AN</b>	ANTHRACITE	<b>4K</b>	4000K
<b>BI</b>	WHITE		

on request:

<b>CO</b>	CORTEN
<b>BR</b>	BRONZE



K<sup>3</sup> WRITER

THE SERIES

