

Outdoor luminaire for wall installation

Completely matt black inside to avoid any unwanted flare

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: LED unit

Rear cable entry

Color matching stainless steel Allen screws

Finish with double painting after anti-corrosion treatments:
epoxy-based primer and polyester powder coating

On request versions (additional code):

D Dimmable version

Dimensions	160 x 160 x 182 mm
Light Source	LED
Multiple Sources	2x
Power	12.8 W
Voltage/Frequency	220-240 V 50/60 Hz
Light output source	1280 lm
LUMEN OUTPUT	336 lm
System efficiency	26 lm/W
Color Rendering Index – CRI	85
LED energy class	F
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	4.19 kg
Certifications	CE UK CA

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
AN ANTHRACITE
BI WHITE

COLOUR TEMP.

3K 3000K
4K 4000K

OPTIC

standard 70°

on request:






CO CORTEN
BR BRONZE

K³ WRITER double emission LED 2X6.4W 2X70°

1008



ACCESSORIES

<p>K³ WRITER LENS FOR 1 BLADE</p>  <p>1091</p>	<p>K³ WRITER LENS FOR 5 BLADES</p>  <p>1092</p>	<p>K³ WRITER LEAF SHAPER</p>  <p>1093</p>	<p>K³ WRITER 30° SHAPER</p>  <p>1095</p>
<p>K³ WRITER COLOR FILTER</p>  <p>1096</p>			

K³ WRITER THE SERIES

