

Outdoor luminaire for wall installation

Completely matt black inside to avoid any unwanted flare

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: LED unit

Rear cable entry

Color matching stainless steel Allen screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D Dimmable version

3F 3-window version

Dimensions	160 x 160 x 182 mm
Light source	LED
Multiple sources	4x
Wattage	25.6 W
Power supply	220-240 V 50/60 Hz
Light source output	2560 lm
System output	672 lm
System efficiency	26 lm/W
Color Rendering Index – CRI	85
LED energy class	F
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	4.18 kg
Conformity	CE UKCA

CODE OPTIONS

FINISH COLOUR TEMP.

AG	ALUMINIUM GREY	3K	3000K
AN	ANTHRACITE	4K	4000K
BI	WHITE		

on request:


CO	CORTEN
BR	BRONZE

K³ WRITER 4x70° LED 4X6.4W 4X70°

1022



ACCESSORIES

K³ WRITER THE SERIES