

Outdoor luminaire for wall installation  
 Completely matt black inside to avoid any unwanted flare  
 Material: low copper content die-cast aluminium  
 Diffuser: ultra-white transparent tempered glass  
 Built-in driver  
 Light source: LED unit  
 Rear cable entry  
 Color matching stainless steel Allen screws  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- 3F 3-window version

Dimensions	<b>160 x 160 x 182 mm</b>
Light source	<b>LED</b>
Multiple sources	<b>4x</b>
Wattage	<b>25.6 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
Light source output	<b>2560 lm</b>
System output	<b>672 lm</b>
System efficiency	<b>26 lm/W</b>
Color Rendering Index – CRI	<b>85</b>
LED energy class	<b>F</b>
Electrical insulation class	<b>Class II</b>
IP rating	<b>IP 65</b>
Impact resistance rating	<b>IK 08 (5 Joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>4.18 kg</b>
Conformity	<b>CE UK CA</b>

## CODE OPTIONS

### FINISH

**AG** ALUMINIUM GREY  
**AN** ANTHRACITE  
**BI** WHITE

### COLOUR TEMP.

**3K** 3000K  
**4K** 4000K


on request:

**CO** CORTEN  
**BR** BRONZE

# K<sup>3</sup> WRITER 4x70° LED 4X6.4W 4X70°

## 1022

### ACCESSORIES



### K<sup>3</sup> WRITER THE SERIES

