


# K³ WRITER four-emission LED 4X6.4W 4X70°

### 1022







Outdoor luminaire for wall installation

Completely matt black inside to avoid any unwanted flare

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: LED unit

Rear cable entry

Color matching stainless steel Allen screws

Finish with double painting after anti-corrosion treatments: epoxy-based primer and polyester powder coating

On request versions (additional code):

D Dimmable version

**3F** 3 light emissions

Dimensions	160 x 160 x 182 mm
Light Source	LED
Multiple Sources	4x
Power	25.6 W
Voltage/Frequency	220-240 V   50/60 Hz
Light output source	2560 lm
LUMEN OUTPUT	672 lm
System efficiency	26 lm/W
Color Rendering Index - CRI	85
LED energy class	F
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	4.18 kg
Certifications	C€ EŘ

#### **CODE OPTIONS**

FINISH COLOUR TEMP. OPTIC

 AG
 ALUMINIUM GREY
 3K
 3000K
 standard
 70°

 AN
 ANTHRACITE
 4K
 4000K

on request:

ΒI

CO CORTEN BRONZE

WHITE

# K³ WRITER four-emission LED 4X6.4W 4X70°

## 1022

#### **ACCESSORIES**











K<sup>3</sup> WRITER

THE SERIES





