



Outdoor luminaire for wall installation
 Completely matt black inside to avoid any unwanted flare
 Material: low copper content die-cast aluminium
 Diffuser: ultra-white transparent tempered glass
 Built-in driver
 Light source: LED unit
 Rear cable entry
 Color matching stainless steel Allen screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- 3F 3-window version

Dimensions	160 x 160 x 182 mm
Light source	LED
Multiple sources	4x
Wattage	25.6 W
Power supply	220-240 V 50/60 Hz
Light source output	2560 lm
System output	672 lm
System efficiency	26 lm/W
Color Rendering Index – CRI	85
LED energy class	F
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	4.18 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH		COLOUR TEMP.	
AG	ALUMINIUM GREY	3K	3000K
AN	ANTHRACITE	4K	4000K
BI	WHITE		


on request:

- CO** CORTEN
- BR** BRONZE

K³ WRITER 4x70° LED 4X6.4W 4X70°

1022

ACCESSORIES



K³ WRITER THE SERIES

