



Outdoor luminaire for wall installation
 Material: low copper content die-cast aluminium
 UV resistant polycarbonate diffuser, flush with the frame
 Built-in driver
 Light source: LED unit
 Rear cable entry
 Color matching stainless steel Allen screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

Dimensions	100 x 100 x 102 mm
Light source	LED
Wattage	3 W
Power supply	100-240 V 50/60 Hz
Light source output	300 lm
System output	200 lm
System efficiency	67 lm/W
Color Rendering Index – CRI	80
LED energy class	C (4000K), D (2700K), D (3000K)
LED lifetime	L70 B50 > 60.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	1 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH		COLOUR TEMP.	
AG	ALUMINIUM GREY	27K	2700K
AN	ANTHRACITE	3K	3000K
BI	WHITE	4K	4000K

on request:

CO	CORTEN
BR	BRONZE

ACCESSORIES



K³ MINILED

THE SERIES

