



Outdoor luminaire for wall installation
 Material: low copper content die-cast aluminium
 UV resistant polycarbonate diffuser, flush with the frame
 Built-in driver
 Light source: LED unit
 Rear cable entry
 Color matching stainless steel Allen screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

15 Optic 15°

| | |
|--|--|
| Dimensions | 100 x 100 x 102 mm |
| Light source | LED |
| Multiple sources | 2x |
| Wattage | 6 W |
| Power supply | 100-240 V 50/60 Hz |
| Light source output | 600 lm |
| System output | 72 lm |
| System efficiency | 12 lm/W |
| Color Rendering Index – CRI | 80 |
| LED energy class | C (4000K), D (2700K), D (3000K) |
| LED lifetime | L70 B50 > 60.000 h |
| Standard Deviation Color Matching (SDCM) | MacAdam step 3 |
| Electrical insulation class | Class II |
| IP rating | IP 65 |
| Impact resistance rating | IK 10 (20 joules) |
| Norms | EN 60598-1 +2-1 |
| Weight | 1 kg |
| Conformity | CE UK CA |

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
AN ANTHRACITE
BI WHITE

COLOUR TEMP.


27K 2700K
3K 3000K
4K 4000K

on request:

CO CORTEN
BR BRONZE



ACCESSORIES



K³ MINILED

THE SERIES

