



Outdoor luminaire for wall installation  
 Material: low copper content die-cast aluminium  
 UV resistant polycarbonate diffuser, flush with the frame  
 Built-in driver  
 Light source: LED unit  
 Rear cable entry  
 Color matching stainless steel Allen screws  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

15 Optic 15°

Dimensions	<b>100 x 100 x 102 mm</b>
Light source	<b>LED</b>
Multiple sources	<b>2x</b>
Wattage	<b>6 W</b>
Power supply	<b>100-240 V   50/60 Hz</b>
Light source output	<b>600 lm</b>
System output	<b>72 lm</b>
System efficiency	<b>12 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>C (4000K), D (2700K), D (3000K)</b>
LED lifetime	<b>L70 B50 &gt; 60.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class II</b>
IP rating	<b>IP 65</b>
Impact resistance rating	<b>IK 10 (20 joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>1 kg</b>
Conformity	<b>CE UK CA</b>

## CODE OPTIONS

### FINISH

**AG** ALUMINIUM GREY  
**AN** ANTHRACITE  
**BI** WHITE

### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K

on request:



ACCESSORIES



**K<sup>3</sup> MINILED**

THE SERIES

