

Outdoor luminaire for wall installation
 Material: low copper content die-cast aluminium
 UV resistant polycarbonate diffuser, flush with the frame
 Built-in driver
 Light source: LED unit
 Rear cable entry
 Color matching stainless steel Allen screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

| | |
|--|--|
| Dimensions | 100 x 100 x 102 mm |
| Light source | LED |
| Multiple sources | 4x |
| Wattage | 12 W |
| Power supply | 100-240 V 50/60 Hz |
| Light source output | 1200 lm |
| System output | 800 lm |
| System efficiency | 67 lm/W |
| Color Rendering Index – CRI | 80 |
| LED energy class | C (4000K), D (2700K), D (3000K) |
| LED lifetime | L70 B50 > 60.000 h |
| Standard Deviation Color Matching (SDCM) | MacAdam step 3 |
| Electrical insulation class | Class II |
| IP rating | IP 65 |
| Impact resistance rating | IK 10 (20 joules) |
| Norms | EN 60598-1 +2-1 |
| Weight | 0.98 kg |
| Conformity | CE UK CA |


CODE OPTIONS

| FINISH | | COLOUR TEMP. | |
|-----------|----------------|--------------|-------|
| AG | ALUMINIUM GREY | 27K | 2700K |
| AN | ANTHRACITE | 3K | 3000K |
| BI | WHITE | 4K | 4000K |

on request:



ACCESSORIES



K³ MINILED

THE SERIES

