

Outdoor luminaire for wall/ground installation
 Material: low copper content die-cast aluminium
 Diffuser: ultra-white transparent tempered glass
 Built-in driver
 Light source: LED unit
 Rear cable entry
 Color matching stainless steel Allen screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D Dimmable version

Dimensions	160 x 160 x 182 mm
Light source	LED
Wattage	11 W
Power supply	220-240 V 50/60 Hz
Light source output	1405 lm
System output	1060 lm
System efficiency	96 lm/W
Color Rendering Index – CRI	80
LED energy class	E (3000K), E (4000K), F (2700K)
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	4.1 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
AN ANTHRACITE
BI WHITE



COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

on request:

CO CORTEN
BR BRONZE

ACCESSORIES



K³ POWER THE SERIES

