

Outdoor luminaire for wall/ground installation  
 Material: low copper content die-cast aluminium  
 Diffuser: ultra-white transparent tempered glass  
 Built-in driver  
 Light source: LED unit  
 Rear cable entry  
 Color matching stainless steel Allen screws  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

**D** Dimmable version

|  |                             |
|--|-----------------------------|
| Dimensions                               | <b>160 x 160 x 182 mm</b>   |
| Light source                             | <b>LED</b>                  |
| Wattage                                  | <b>18 W</b>                 |
| Power supply                             | <b>220-240 V   50/60 Hz</b> |
| Light source output                      | <b>2761 lm</b>              |
| System output                            | <b>1900 lm</b>              |
| System efficiency                        | <b>106 lm/W</b>             |
| Color Rendering Index – CRI              | <b>80</b>                   |
| LED energy class                         | <b>E</b>                    |
| LED lifetime                             | <b>L80 B10 86.000 h</b>     |
| Standard Deviation Color Matching (SDCM) | <b>MacAdam step 3</b>       |
| Electrical insulation class              | <b>Class II</b>             |
| IP rating                                | <b>IP 65</b>                |
| Impact resistance rating                 | <b>IK 08 (5 Joules)</b>     |
| Norms                                    | <b>EN 60598-1 +2-1</b>      |
| Weight                                   | <b>4.1 kg</b>               |
| Conformity                               | <b>CE UK CA</b>             |



### CODE OPTIONS

| FINISH    |                | COLOUR TEMP. |       |
|-----------|----------------|--------------|-------|
| <b>AG</b> | ALUMINIUM GREY | <b>27K</b>   | 2700K |
| <b>AN</b> | ANTHRACITE     | <b>3K</b>    | 3000K |
| <b>BI</b> | WHITE          | <b>4K</b>    | 4000K |

on request:

|           |        |
|-----------|--------|
| <b>CO</b> | CORTEN |
| <b>BR</b> | BRONZE |

ACCESSORIES



**K<sup>3</sup> POWER** THE SERIES

