

Outdoor luminaire for wall/ground installation
 Material: low copper content die-cast aluminium
 Diffuser: ultra-white transparent tempered glass
 Built-in driver
 Light source: LED unit
 Rear cable entry
 Color matching stainless steel Allen screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D Dimmable version

| | |
|--|-----------------------------|
| Dimensions | 160 x 160 x 182 mm |
| Light source | LED |
| Wattage | 18 W |
| Power supply | 220-240 V 50/60 Hz |
| Light source output | 2761 lm |
| System output | 1900 lm |
| System efficiency | 106 lm/W |
| Color Rendering Index – CRI | 80 |
| LED energy class | E |
| LED lifetime | L80 B10 86.000 h |
| Standard Deviation Color Matching (SDCM) | MacAdam step 3 |
| Electrical insulation class | Class II |
| IP rating | IP 65 |
| Impact resistance rating | IK 08 (5 Joules) |
| Norms | EN 60598-1 +2-1 |
| Weight | 4.1 kg |
| Conformity | CE UK CA |




CODE OPTIONS

| FINISH | | COLOUR TEMP. | |
|-----------|----------------|--------------|-------|
| AG | ALUMINIUM GREY | 27K | 2700K |
| AN | ANTHRACITE | 3K | 3000K |
| BI | WHITE | 4K | 4000K |

on request:

| | |
|-----------|--------|
| CO | CORTEN |
| BR | BRONZE |

ACCESSORIES



K³ POWER THE SERIES

