



Outdoor luminaire for wall/ground installation  
 Material: low copper content die-cast aluminium  
 Diffuser: ultra-white transparent tempered glass  
 Built-in driver  
 Light source: LED unit  
 Rear cable entry  
 Color matching stainless steel Allen screws  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

**D** Dimmable version

Dimensions	<b>160 x 160 x 182 mm</b>
Light source	<b>LED</b>
Wattage	<b>18 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
Light source output	<b>2761 lm</b>
System output	<b>1690 lm</b>
System efficiency	<b>94 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>E</b>
LED lifetime	<b>L80 B10 86.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class II</b>
IP rating	<b>IP 65</b>
Impact resistance rating	<b>IK 08 (5 Joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>4.1 kg</b>
Conformity	<b>CE UK CA</b>

## CODE OPTIONS

FINISH		COLOUR TEMP.	
<b>AG</b>	ALUMINIUM GREY	<b>27K</b>	2700K
<b>AN</b>	ANTHRACITE	<b>3K</b>	3000K
<b>BI</b>	WHITE	<b>4K</b>	4000K

on request:

<b>CO</b>	CORTEN
<b>BR</b>	BRONZE

**K<sup>3</sup> POWER** THE SERIES

