



Outdoor luminaire for wall/ground installation
 Material: low copper content die-cast aluminium
 Diffuser: ultra-white transparent tempered glass
 Built-in driver
 Light source: LED unit
 Rear cable entry
 Color matching stainless steel Allen screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D Dimmable version

| | |
|--|-----------------------------|
| Dimensions | 160 x 160 x 182 mm |
| Light source | LED |
| Multiple sources | 2x |
| Wattage | 36 W |
| Power supply | 220-240 V 50/60 Hz |
| Light source output | 5522 lm |
| System output | 3800 lm |
| System efficiency | 106 lm/W |
| Color Rendering Index – CRI | 80 |
| LED energy class | E |
| LED lifetime | L80 B10 86.000 h |
| Standard Deviation Color Matching (SDCM) | MacAdam step 3 |
| Electrical insulation class | Class II |
| IP rating | IP 65 |
| Impact resistance rating | IK 08 (5 Joules) |
| Norms | EN 60598-1 +2-1 |
| Weight | 4.4 kg |
| Conformity | CE UK CA |

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
AN ANTHRACITE
BI WHITE




COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

on request:

CO CORTEN
BR BRONZE

ACCESSORIES



K³ POWER THE SERIES

