


RGBW K³ double emission LED RGBW 2X32W 2X30°

1185







Outdoor luminaire for wall installation

Completely matt black inside to avoid any unwanted flare

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: 3 RGBW LEDs and a device to receive DMX standard 512 signal sent from the control unit 1181 or another compatible unit. The contained light source is intended for use in applications requiring high-quality coloured light

Rear cable entry

Color matching stainless steel Allen screws

Up to 32 luminaires can be connected to each control unit

Finish with double painting after anti-corrosion treatments: epoxy-based primer and polyester powder coating

On request versions (additional code):

Multi-channel setting

Dimensions	160 x 160 x 182 mm	
Light Source	LED RGBW	
Multiple Sources	2x	
Extra info W	max	
Power	64 W	
Voltage/Frequency	220-240 V 50/60 Hz	
Light output source	1980 lm	
LUMEN OUTPUT	1380 lm	
System efficiency	23 lm/W	
Electrical insulation class	Class I	
IP rating	IP 65	
Impact resistance rating	IK 08 (5 Joules)	
Norms	EN 60598-1 +2-1	
Weight	4.2 kg	
Certifications	C€ FR	

CODE OPTIONS

FINISH		OPTIC	
AG	ALUMINIUM GREY	standard	30°
AN BI	ANTHRACITE WHITE	optional optics	
on req	uest:	10 54	10° 54°
CO BD	CORTEN		



RGBW K³ double emission LED RGBW 2X32W 2X30°

1185



RGBW

THE SERIES

