
RGBW K³ 2x LED RGBW 2X32W

1185





Outdoor luminaire for wall installation

Completely matt black inside to avoid any unwanted flare

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: 3 RGBW LEDs and a device to receive DMX standard 512 signal sent from the control unit 1181 or another compatible unit. The contained light source is intended for use in applications requiring high-quality coloured light

Rear cable entry

Color matching stainless steel Allen screws

Up to 32 luminaires can be connected to each control unit

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):
Multi-channel setting

Dimensions	160 x 160 x 182 mm
Light source	LED RGBW
Multiple sources	2x
Light source info	max
Wattage	64 W
Power supply	220-240 V | 50/60 Hz
Light source output	1980 lm
System output	1380 lm
System efficiency	23 lm/W
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	4.2 kg
Conformity	CE UKCA

CODE OPTIONS

FINISH

AG	ALUMINIUM GREY
AN	ANTHRACITE
BI	WHITE

on request:

CO	CORTEN
BR	BRONZE

OPTIC

standard	30°

optional optics

10	10°
54	54°

Goccia Illuminazione srl
via E.Fermi 59/65 - 25020 Poncarale (BS) Italy
+39 030 2640761 - info@www.goccia.it

RGBW K³ 2x LED RGBW 2X32W

1185

ACCESSORIES

ACCESSORIES
SIGNAL GENERATOR



1181

RGBW THE SERIES

